# **Spherical roller bearings**

### R00 GR030220 MA030220

# 24056 ECCC3W33XS1VL/5/A5

Main boundary dimensions (mm)			
d	280		
D	420		
В	140		

Technical data				
Pagin land ratings (IAN)		C <sub>r</sub>	2234	
Basic load ratings (kN)	Stat.	C <sub>or</sub>	3760	
Mass (kg)			70,1	
Cage material			Pressed steel	
	r,		4,0	
Dadius min (mm)	r <sub>2</sub>		4,0	
Radius min (mm)	r <sub>3</sub>		-	
		r <sub>4</sub>	-	
Precision class			P0	
е			0,31	
Bearing clearance (mm)			C3	

# r<sub>2</sub>min r<sub>2</sub>min

## **Technical notes**

- Reference speed 860 rpm. Limiting speed 1250 rpm. Victory Line premium class
- Optimized internal design with reinforced execution. Pressed steel cage
- Annular groove and lubrication holes in outer ring
- Bainite hardened rolling elements
- Bearing rings heat stabilized for operating temperatures up to 200 °C
- Quality Certificate of Conformance Data Sheet included
- For general industry purpose

The sketch is for reference only and may not be representative or indicative of the actual product. Sketch scale is free. Also refer to RKB Affidavit of Conformance for related compliance to International Standards.

Every care has been taken to ensure the accuracy of the information in the present drawing, but no liability can be accepted for any errors or omissions contained herein, or in case losses and/or damages (direct, indirect, consequential) should occur. RKB Bearing Industries reserves the right of any amendment without notice.

